

Ns. rif BRC 900463 and BRC 000545

STARLINE S.P.A.

Via F. Baracca, 30
 24060 S.PAULO d'ARGON
 (BERGAMO) - ITALY

Vs. rif FIRE TEST DOCUMENT 02/90 Rev.0

Data December 3rd, 1990

This is to certify that the following no. 22 Starline ball valves, selected on random basis from manufacturer's current production have satisfactorily passed FIRE TEST according to BS 6755 PART 2:1987 APPX. A&B, API 607 III ISSUE:1985 and API 6FA:1985.

STARLINE BALL VALVE TYPE: MASTER STAR No.3

LLOYD'S TEST REPORT	DATE	STARLINE FIRE TEST	VALVE TESTED			VALVE SIZE QUALIFIED	RATING QUALIFIED	
			SIZE	CLASS	TYPE		ASME/ANSI	PN
BRC 000545/6	16/11/90	239/90-A	1/2	150Lbs	233SGV.	1/2-3/4-1	150/300	16/25/40
BRC 000545/7	16/11/90	240/90-A	1/2	150Lbs	236SGV..	1/2-3/4-1	150/300	16/25/40
BRC 000545/3	09/11/90	236/90-A	1.1/4	150Lbs	233SGV.	1.1/4-1.1/2-2-2.1/2	150/300	16/25/40
BRC 000545/5	16/11/90	238/90-A	1.1/4	150Lbs	236SGV..	1.1/4-1.1/2-2-2.1/2	150/300	16/25/40
BRC 900463/12	06/10/89	231/89-A	1/2	600Lbs	233SGV.	1/2-3/4-1	600/800/900	-
BRC 900463/11	06/10/89	230/89-A	1/2	600Lbs	236SGV..	1/2-3/4-1	600/800/900	-
BRC 900463/8	29/09/89	227/89-A	1.1/4	600Lbs	233SGS.	1.1/4-1.1/2-2-2.1/2	600/800/900	-
BRC 900463/7	29/09/89	226/89-A	1.1/4	600Lbs	236SGS..	1.1/4-1.1/2-2-2.1/2	600/800/900	-

STARLINE BALL VALVE TYPE: SUPER STAR No. 1

BRC 900463/10	06/10/89	229/89-A	1/2	800Lbs	213SGV.	1/2-3/4-1	800/900/1500	-
BRC 900463/9	06/10/89	228/89-A	1/2	800Lbs	216SGV..	1/2-3/4-1	800/900/1500	-
BRC 900463/6	29/09/89	225/89-A	1.1/4	800Lbs	213SGS.	1.1/4-1.1/2-2-2.1/2	800/900/1500	-
BRC 900463/5	29/09/89	224/89-A	1.1/4	800Lbs	216SGS..	1.1/4-1.1/2-2-2.1/2	800/900/1500	-
BRC 900463/14	13/10.89	233/89-A	2.1/2	300Lbs	213SGV.	2.1/2-3-4-5	300/600	25/40
BRC 900463/13	13/10/89	232/89-A	2.1/2	300Lbs	216SGV..	2.1/2-3-4-5	300/600	25/40
BRC 000545/8	16/11/90	241/90-A	2	300Lbs	213SGV.	2-2.1/2-3-4	300/600	25/40
BRC 000545/4	09/11/90	237/90-A	2	300Lbs	216SGV..	2-2.1/2-3-4	300/600	25/40
BRC 000545/2	09/11/90	235/90-A	2	150Lbs	213SGV.	2-2.1/2-3-4	150/300	16/25/40
BRC 000545/1	09/11/90	234/90-A	2	150Lbs	216SGV..	2-2.1/2-3-4	150/300	16/25/40

STARLINE BALL VALVE TYPE: MEGASTAR No.6

BRC 900463/3	22/09/89	222/89-A	1/2	1500Lbs	163DGG.	1/2-3/4-1	1500/2500	-
BRC 900463/4	22/09/89	223/89-A	1/2	1500Lbs	166DGG..	1/2-3/4-1	1500/2500	-
BRC 900463/2	22/09/89	221/89-A	1	1500Lbs	163DGG.	1-1.1/2-2	1500/2500	-
BRC 900463/1	29/09/89	220/89-A	1	1500Lbs	166DGG..	1-1.1/2-2	1500/2500	-

VALVE TESTED IN	MATERIALS QUALIFIED FOR SOFT SEATED BALL VALVES
• A105/F316 material	Carbon steel - All ferritic steels - ASME P.n.1 - etc.
• F316/F316 material	All Austenitic steels - ASME P n.8 - etc.

G. Dall'Acqua

Surveyor to Lloyd's Register